



SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

- Stitched combo mat (2stages, +/-45degree),
- Stitched combo mat (0/90 degree)
- Stitched combo mat (multi-axial)
- Stitched chopped strand mat
- UD(hot-melt)
- Unidirectional fabric
- Woven roving chopped strand mat

SUPPLIER INFORMATION :

AMP COMPOSITES CO.,LTD
 No.26,Xingfa Road,Longxiang Industrial Area,Tongxiang,Zhejiang 314500, China
 Tel: +86-573-88793188 88792323
 Fax: +86-573-88793636
 Email: sales@ampcomposites.com

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENT

Ingredients of Products:

Product Name	Glass, %	Stitching yarn , %	Loss on ignition %	Moisture , %
Stitched combo mat (2stages, +/-45degree)	≥98	≤2	≤1.98	≤0.05
Stitched combo mat (0/90 degree)	≥97	≤3	≤2.23	≤0.05
Stitched combo mat (multi-axial)	≥98.5	≤1.5	≤1.87	≤0.06
Stitched chopped strand mat	≥98	≤2	≤1.98	≤0.06

UD (hot-melt)	≥98	≤2	≤1.98	≤0.04
Unidirectional fabric	≥98	≤2	≤1.87	≤0.04
Woven roving chopped strand mat	≥98	≤2	≤1.75	≤0.06

SECTION 3 – HAZARDS IDENTIFICATION

Classification of Hazards:

No information available.

Routes of Entry:

Ingestion, inhalation, skin and eye contact.

Health Effects:

Ingestion: Ingestion of the material is unlikely. However, ingestion of the material may cause gastrointestinal disturbance.

Inhalation: Breathing fiberglass dusts and particulates may cause irritation of the nose, throat and respiratory tract.

Skin contact: Fiberglass dusts and particulates may cause temporary irritation.

Eye contact: Fiberglass dusts and particulates may cause temporary irritation to the eyes.

Environmental Effects:

Long-term exposure to fiberglass environment may cause temporary effects.

Inflammation and Explosion Hazards:

No information available.

SECTION 4 – FIRST-AID MEASURES

Skin Contact:

If irritation occurs to the skin, rinse with soap and water. Make sure to refrain from rinsing with warm water since warm water will make the skin pores open to allow fiberglass to penetrate more deeply. If fiberglass penetrates the skin, use a wash cloth to help pull out the fiberglass. To avoid further irritation, do not rub or scratch affected skin. If irritation persists, get medical help. Make sure to refrain from using compressed air to remove fiberglass from the skin.

Eye Contact:

Immediately flush eyes with clean water for at least 15 minutes. If irritation persists, get medical help.

Inhalation:

If inhaled, immediately remove the affected person to fresh air. If irritation persists, get medical help.

Ingestion:

Normally, ingestion of this material is unlikely. If it does occur, watch the person for several days to make sure that gastrointestinal disturbance does not occur. Do not let the person vomit unless required by medical personnel. If disturbance persists, get medical help.

SECTION 5 – FIRE-FIGHTING MEASURES**Flammability Classification:**

Non-flammable. But the size and packing material may burning.

Hazardous Combustion Products:

Primary combustion products are carbon monoxide, hydrogen, carbon dioxide and water. Other undetermined compounds can be released in small quantities.

Fire-Fighting Methods:

Use dry chemical, foam, carbon dioxide and water as extinguishing media.

Fire-Fighting Instructions:

Fire fighters must use self-contained breathing apparatus and wear full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

In case of release to land, the material should be scooped up as waste and put into a special container and stored in a designated area. In case of release of water, the material will sink and disperse along the bottom of waterways or ponds and can not be easily removed after it is waterborne. However, the material is non-hazardous in water.

SECTION 7 – HANDLING AND STORAGE**Handling:**

Try to prevent the packing material from be damaged and keep the product inside the packing material to minimize the generation of dusts. Maintain a clean work environment and avoid generation of fiberglass fragments from improper handling.

Storage:

No special requirements for storage.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Highest Permissible Concentration:

National and international hygiene standards are as follows:

Component	Permissible Exposure Limit of OSHA (8-hr Average Weight)	Permissible Exposure Limit of ACGIH (8 hr Average Weight)
Non-respirable fibers and particulates	5 mg/m ³ (Total dust)	5 mg/m ³ (Inhalable fraction)
Respirable particulates	5 mg/m ³ (Respirable fraction)	3 mg/m ³ (Particles not otherwise classified)
Size of respirable particulates	None established	None established

Engineering Control:

Production areas are closed off and a required relative humidity is maintained.

Respiratory Protection:

Wear a suitable mask when working in an environment where dust concentration is high.

Eye Protection:

Wear safety glasses and face shield.

Body Protection:

Normal loose working clothing (long-sleeved shirts and long pants) is recommended. Skin irritation occurs primarily at the contact areas such as around the neck and waist.

Hand Protection:

Wear gloves. Skin irritation occurs primarily at the contact areas such as wrists and between the fingers.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Product Appearance and Properties:

White or off-white solid; No odor.

pH Value:

Flash Point:

Not applicable

Ignition Temperature:

Not applicable.

Melting Point:

>800°C.

Boiling Point:

Not applicable.

Relative Density:

2.6 Times that of water.

Relative Vapor Density:

Not applicable

Product Use:

Fiberglass is an inorganic nonmetal material and is used as reinforcement for thermoplastic and thermosetting resins.

Not applicable

Explosion Upper Limit:

Not applicable

Explosion Lower Limit:

Not applicable

Solubility (in Water):

Insoluble

SECTION 10 – STABILITY AND REACTIVITY

Stability:

This is a Stable material.

Materials to Avoid:

None.

Conditions to avoid:

None.

Hazardous Polymerization

Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Acute Toxicity:

None.

Irritability:

Fiberglass dusts may cause irritation to skin and eye. Ingestion of fiberglass may cause irritation to the throat, stomach and gastrointestinal tract. Inhalation may cause coughing, sneezing and nose and throat irritation. Experience indicates that inhalation of a large amount of fiberglass may cause difficulty in breathing, congestion and chest tightness.

Carcinogenicity:

The International Agency for Research on Cancer (IARC), agency of the World Health Organization (WHO), has determined that fiberglass is a non-carcinogenic material because the evidence is inadequate to prove that fiberglass can cause humans and experimental animals to develop cancer.

SECTION 12 – ECOLOGICAL INFORMATION

No data available for this product. Fiberglass products are not listed as a material harmful to animals, plants and fish.

SECTION 13 – DISPOSAL CONSIDERATIONS

RCRA Hazard class:

Non-hazardous.

Disposal Instructions:

Dispose waste material according to local environmental regulations.

SECTION 14 – TRANSPORT INFORMATION

Classification and Code of Hazards:

None.

UN Code:

None.

Packing Mark:

None.

Packing Category:

None.

Packing Method:

None.

Transport Instructions:

Rolling and moisture should be avoided in transit.

SECTION 15 – REGULATORY INFORMATION

SARA title III :

Hazard categories :

Acute health:	Yes
Chronic health:	No
Fire hazard:	No
Pressure hazard:	No
Reactivity hazard:	No

Reportable ingredients:

Sec.302/304:	None
Sec.313:	None

Clean Air Act:

No ingredient is listed.

WHMIS(Canada) Status :

No controlled.

WHMIS classification(s):

None.

SECTION 16 – OTHER INFORMATION

Preparation Date:

Jun.2020

Prepared by:

Quality management department

AMP COMPOSITES CO.,LTD

No.26,Xingfa Road,Longxiang Industrial Area,Tongxiang,Zhejiang 314500, China

Tel: +86-573-88793188 88792323

Fax: +86-573-88793636

Email: sales@ampcomposites.com Web: www.ampcomposites.com